



# TIG 200

Order Code: **EPT-200**

## Key Features


- Rugged, ergonomic design
- **Dash-Arc**
- **Smart Lift TIG**
- Full featured DC TIG parameters
- **ABAP: Active Balancing Air Passage**
- **Smart gas** for optimised shielding gas consumption
- Fan on demand
- Voltage Reduction Device (VRD)
- Key power electronic component protection
- Overcurrent and overheat protection
- **Complete with protective case and TIG leads**



## Technical Data

EPT-200		
Input voltage	AC 230V 50/60Hz	
No load voltage	62V	
TIG	leff	12.1A
	Rated input power	6.2kVA
	Current range	5-200A
MMA	Rated duty cycle @ 40°C	20%
	leff	12.9A
	Rated input power	6.7kVA
	Current range	10-160A
	Rated duty cycle @ 40°C	20%
Efficiency	86%	
Power factor	0.68	
Idle state power	25W	
Protection class	IP23S	
Insulation class	H	
Dimensions LxWxH	413 x 150 x 311mm	
Weight	7.5Kg	
Recommended generator size	9kVA	

\* Generator must have AVR



### Standard Accessories

- Protective Carry Case
- 4m TIG Torch (JE79-ERGO)
- Argon Regulator
- Gas Hose